

[10191/4286]

METHOD FOR THE OUTPUT OF TEXT INFORMATION VIA A DISPLAY

Background Information

The present invention is directed to a method for output of text information via a display in a driver information system of the generic type according to the independent patent claim.

- 5 Driver information systems that output text information via a display are known in the form of receivers for traffic messages transmitted by radio, e.g., from DE 35 36 820 C2. DE 35 36 820 C2 and ISO standards 14819-1, -2 and -3 describe, among other things, a method for encoded transmission of
- 10 traffic messages in which a present message is broken down into elements at the transmitter end, the elements being encoded according to a catalog of standardized message elements and these codes then being transmitted. At the receiver end, the received codes are assigned to message
- 15 elements stored in a table and thus the traffic message composed of message elements assigned to the codes is displayed on the display. Memory media that are frequently replaceable such as CD-ROMs and DVDs in particular are used for storing the decoding table.
- 20 Today's receivers for traffic messages of the type described here often have a display having a capacity of four to five lines, usually having at least 16 characters each. To be able to use the same decoding table and thus the same data medium for decoding traffic message codes received via radio in a
- 25 plurality of receivers, the message elements stored there are usually limited to a length of 16 characters. If the display capacity of such a driver information system is to be utilized optimally, decoding tables adapted to a particular display

capacity of the particular device are needed at the present time.

Advantages of the Invention

The method and the data medium according to the present invention having the features of the independent patent claims have the advantage that despite the use of only a single database for text information to be output, the particular display capacity in each case is regularly utilized at least approximately optimally for a plurality of different types of equipment having different display capacities. Thus essentially a single data medium is sufficient for a plurality of different types of driver information systems. Due to the associated high number of universal data media involved, it is possible to greatly reduce their manufacturing costs. In addition, the same data medium may also alternately be used for different driver information systems, e.g., in two vehicles of the same owner, multiple service vehicles of one employer, or different rental cars of one rental car company. Under some circumstances, this reduces the acquisition costs of the data media required for operation of the driver information systems.

Advantageous embodiments and refinements of the present invention are derived from the dependent patent claims, which are explained in greater detail in the description of the exemplary embodiments.

Drawing

Exemplary embodiments of the present invention are illustrated in the figure and explained in greater detail below. The figure shows a block diagram of a driver information system according to the present invention for implementation of the method according to the present invention having an

information data medium 24 for use in the driver information system.

Description of the Exemplary Embodiments

A basic idea of the present invention is to break down all
5 information to be output on a display of a device, in
particular a driver information system for a motor vehicle,
into at least two basic components, providing an abbreviation
for each basic component in addition to a full text version,
i.e., storing it in a memory of the device, e.g., a CD-ROM or
10 the like. To adapt the information output to the display
capacity of the display of the device, the particular
abbreviation is then output instead of the full text version
of an information component, if necessary. If information is
made up of information elements, as described at the outset in
15 the case of TMC traffic messages, for example, then for output
of information made up of information elements, the breakdown
may advantageously also be applied to the individual
information elements, for which then, if necessary, full text
versions or abbreviated versions of the information element
20 components are output.

The figure shows a block diagram of a driver information system 2 according to the present invention for implementation of the method according to the present invention.

In the present case, driver information system 2 is a receiver
25 for traffic messages transmitted by the TMC standard of ISO
14819-1, -2 and -3 within the RDS signal (Radio Data System)
by radio without any restriction of general validity. These
signals are transmitted by a transmitter 1 as part of a radio
signal 11 over a VHF radio frequency by a known method. This
30 frequency is modulated with the radio data signal, among other
things. Radio signal 11 is picked up by a receiving antenna 20
of driver information system 2 and demodulated in a

demodulator 21. The signal containing the actual information of interest, here applied at the output of demodulator 21, is sent to a decoder 22 for decoding the RDS-TMC signal. The signal containing the actual traffic message codes applied at the output of decoder 22 is sent to an output control unit 23.

Output control unit 23 has the function of adapting text information to be displayed on a display 25 to the capacity of display 25 and performing the display. In the case of driver information system 2 described here, the text information to be displayed is traffic messages obtained from the received RDS-TMC codes. Output control unit 23 here accesses a decoder table 24 in which information elements and/or message elements are assigned to the codes. Decoding table 24 is implemented in the form of a replaceable data medium, e.g., in the form of a CD-ROM here, which is accessed via a corresponding CD-ROM reader.

Data medium 24 contains the text information to be displayed on the display. Each information element on the data medium is divided into at least two components, preferably three components in the case of the present exemplary embodiment, namely a prefix, a body, and a suffix.

This division is explained below on the basis of the TMC location code list according to ISO 14819-3. Important locations along the most important traffic routes are stored as location codes in the TMC location code list. Highway entrances and exits in particular, highway cloverleafs and intersections, rest sites, important node points of interstate highways, etc., are encoded using location codes. At least one street name and one place name are assigned to each of these location codes, the place name in particular being provided in text form on a display 25 of the device for output of the traffic message or in acoustic form via a voice synthesizer

unit 26 of the device. Such a location name is an information element in the sense of the present invention.

In the following three examples, the name of the encoded location as an information element is broken down into three components, i.e., prefix 2411, body 2412 and suffix 2413, these three components being stored on data medium 24, where they are assigned to particular location code 241. In addition, abbreviated components "shortened prefix" 2414, "shortened body" 2415, and "shortened suffix" 2416 are assigned to each of the three components and saved. Each of the three components is not necessarily present nor is it necessarily true that a corresponding abbreviation is present for each component present. In the sense of the patent claims, however, a component that is not present or an abbreviation that is not present, i.e., shortened prefix 2414, shortened body 2415, or shortened suffix 2416, is understood to refer to the corresponding component, then with the content "". All components and their particular abbreviations are addressed jointly on the data medium through particular location code 241 and/or event code 242.

Three examples of the breakdown of one location name of the location code list into prefix, body, and suffix as well as the particular abbreviated variant of the corresponding information element are given below.

25 1) "Berlin-Reinickendorf"

Prefix = "Berlin",	Shortened Prefix = "B-"
Body = "Reinickendorf"	Shortened Body = ""
Suffix = ""	Shortened Suffix = ""

2) "Frankfurt am Main - Heddernheim"

30 Prefix = "Frankfurt am Main"	Shortened Prefix = "FfM-"
Body = "Heddernheim"	Shortened Body = ""
Suffix = ""	Shortened Suffix = ""

3) "Braunschweig - Hamburger Strasse"

Prefix = "Braunschweig"	Shortened Prefix = "BS-"
Body = "Hamburger"	Shortened Body = ""
Suffix = "Strasse"	Shortened Suffix = "Str."

5 Similarly, this breakdown is also provided for the event list according to ISO 14819-2, for example, in which event texts likewise assigned to event codes (events) are stored for text output on a display or for acoustic output. For example, the following text is assigned to event code 1392 (reference
10 number 242): "Warning, a driver is approaching in the wrong lane! Do not pass! Caution on lanes going in both directions! We will report when the danger has passed." Such an event text also constitutes an information element in the sense of the present invention. According to the present invention, this is
15 broken down on the data medium into the components

Prefix 2421 = "Warning"

Body 2422 = "A driver is approaching in the wrong lane! Do not pass! Caution on lanes going in both directions! We will report when the danger has passed."

20 Suffix 2423 = ""

The abbreviations stored for this in addition include

Shortened prefix 2424 = "Warning."

Shortened body 2425 = "Driver in wrong lane"

Shortened suffix 2426 = ""

25 The purpose of this division of information, i.e., information elements stored on the data medium, here in particular event and location designators, is to adapt the information output to the display capacity of display 25. They may differ in particular in the number of text lines available for output as
30 well as the number of characters per line and/or the font used for the display, namely proportional or non-proportional font, for example.

As a function of these parameters, display control unit 23 controls the following message text output, depending on the display capacity.

1) Message written out in full over four lines:

5

On A 392
Braunschweig-Watenbüttel in the direction of Braunschweig-
Hamburger Strasse
between Braunschweig-Celler Strasse and AS Braunschweig-
10 Hamburger Strasse junctions
2 km congestion

2) Abbreviated version:

15 A 392
BS-Watenbüttel BS-Hamburger Str.
BS-Celler Str. jct. BS-Hamburger Str. jct.
2 km congestion

3) Combination of abbreviated and unabbreviated name
designators over five lines:

20

On A 392
BS-Watenbüttel in direction of BS-Hamburger Str.
Braunschweig-Celler Str. jct.
Braunschweig-Hamburger Str. jct.

25 2 km congestion

The text display of the information, namely traffic messages here, composed of multiple units of information, is displayed in sections, a separate line of display unit 25 being available for each unit of information in the present case.

30 The individual units of information to be displayed include the street affected by a traffic holdup, the section of street affected, including a reference to the direction, the location

of the traffic-relevant event limited by the nearby encoded locations, and the traffic-relevant event itself. Each unit of information mentioned above includes at least one information element, e.g., the unit of information "event" is formed from a single information element, whereas the "direction" as a unit of information includes three subelements, namely a first place name "Berlin-Wedding," a second place name "Berlin-Reinickendorf," and the direction formulated as "in direction of." Each line is made up of an XML character string by display control unit 23. A possible division of the display based on today's receivers of TMC traffic messages would be as follows, for example:

	Description	Example
1st line:	street affected	On A 110
15 2nd line:	direction information	Berlin-Wedding in direction of Berlin- Reinickendorf
3rd line:	place information	Between Achterwehr and Melsdorf junctions
20 4th line:	event	2 km congestion

Each line of display 25 is created from the XML character string generated by display control unit 23, taking into account the maximum line length displayable. If a proportional font is not used, the line length is determined from the maximum number of characters; otherwise it is determined from the maximum number of pixels per line. These values, like the type of font used (proportional/not proportional), are stored for this purpose in each device in display control unit 23 or alternatively they may be checked by display control unit 23.

If the length of a unit of information, namely one line here, to be output currently exceeds the maximum line length displayable on display unit 25 of current driver information system 2, the line length may be abbreviated using the abbreviations of the prefix, body, and/or suffix that have been saved.

The line length is preferably abbreviated according to the following rules:

- 1) Replace the suffix by the shortened suffix if the shortened suffix contains at least one character.
- 2) Replace the prefix by the shortened prefix if the shortened prefix contains at least one character.
- 3) Suppress the suffix and the shortened suffix.
- 4) Suppress output of filler words.
- 5) Replace the body with the shortened body if the shortened body includes at least one character.
- 6) Line break
- 7) Terminate the second line after the maximum number of characters if the original line does not fit into two lines of display unit 25.

Preceding rules 1) through 7) are applied to each unit of information, i.e., to each individual line of information to be output in the present case, starting with the first rule in the order of ascending numbers. As soon as one of the rules has been successful, i.e., the line currently being considered is displayable on the display by applying the rules, the line and/or the unit of information is displayed without taking the other rules into account.

For the case of a possible alternative embodiment such that multiple units of information to be output are displayed in a joint line of display unit 5, it is also possible to provide for one of the rules to first be applied to a first unit of

information of the line, then, if necessary to a second and, optionally, additional units of information of the line before the additional rules are applied in the same way to the units of information of the line if necessary. Application of the
5 rules to one or, if necessary, multiple units of information is terminated when the total length of the units of information to be depicted in the line is less than or equal to the available length of the line. It is thus possible to optimally utilize the available line length in each case.

10 If multiple units of information are output in a joint line, alternatively the above rules may, however, also be applied essentially to the entire line in each case, i.e., jointly to multiple units of information. Alternatively, however, it is
15 in a line for the rules to be processed first for a first unit of information before then being applied to a next unit of information of the line.

It is clear from rules 1) through 7) above that the body of the information or of an information element is regarded as
20 particularly essential for the output. Therefore, in the case of a necessary abbreviation of information components, the prefix and suffix are preferably shortened first and optionally omitted entirely before the body is output in abbreviated form. The sequence in which the rules are applied
25 also indicates that the suffix is regarded as being of lesser significance in comparison with the prefix.

The rules given represent a particularly preferred procedure. Nevertheless, different rules are also possible as well as different sequences in applying the rules. These are also
30 within the scope of the present invention. For example, it is also possible as an alternative to first output the body in the abbreviated version before deleting the prefix and suffix

if the abbreviated version of the body includes at least one character. In particular it is also possible for the interpretation of the information components and their abbreviations on the data medium to be adapted to the rules applied and the order in which they are applied. For example, in the alternative order described here, it is possible for a comparatively detailed and preferably self-explanatory version to be saved for the abbreviated body, whereas very short abbreviations are selected for the suffix in particular, but also the prefix, for example.

The present invention has been explained above on the example of TMC traffic messages, which are usually made up of multiple units of information as described above, namely the street affected, the segment of street including direction information, the location of the event and the event itself, whereby in turn each unit of information includes at least one information element. However, this does not constitute a restriction of the present invention to the display of TMC messages nor to the data structure described here. Moreover, according to the present invention it is also possible for the information not to be made up of information elements but instead for the information itself to constitute the smallest unit of information. In this case, the breakdown into prefix, body, and suffix constituents according to the present invention is applied directly to the information and the display method is also implemented with these constituents.

Therefore, the present invention is not limited to receivers for encoded traffic messages but instead may be applied to any information system having a text information output. Other possible examples of applications include vehicle navigation systems, for example, in which direction of travel information may be displayed in the form of text on a display. Other different applications are also possible and are within the

scope of the present invention. Essentially, the present invention is applicable to any number of devices that generate information to be displayed on a display unit and may be applied to essentially any other information to be displayed.

5 According to one advantageous further development of the present invention, in addition to the text information output via display 25, a acoustic output via a voice synthesizer system having connected loudspeaker 26 may also be provided. For this case, for example, the display may be limited in its
10 display capacity and thus the information may be output in a more or less greatly reduced form, whereas the information may be output acoustically in the complete version. To do so, the display control unit as part of output control unit 23 also accesses the abbreviated versions of prefix, body, and suffix
15 while the output control unit for the acoustic output preferably utilizes the full versions of prefix, body, and suffix for each item of information from data medium 24.

The present invention was explained above on the example of a receiver for traffic messages transmitted over FM radio.

20 However, this does not constitute a restriction of the present invention either to the origin or the type of messages or to the transmission method of medium if transmitted messages are involved. In particular a radio transmission via some other analog or digital radio may be considered for transmission of
25 traffic messages according to the TMC standard; this would include for example the AM-RBDS which is widely used in the U.S. and resembles FM-RDS or DAB (Digital Audio Broadcasting), DVB (Digital Video Broadcasting), or the like. For example, a transmission of traffic messages in a point-to-point method
30 may also be considered, e.g., via GSM (Global System for Mobile Communication) or UMTS mobile radio.

Furthermore, the information need not necessarily be output directly via a display of the receiver or of the device generating the messages. Instead it is also possible for the information to be output via a separate display unit. For
5 example, a handheld computer such as a PDA or the like may be connected as a separate display unit to the device generating the messages or making them available with the connection being over an infrared interface or a Bluetooth interface, and the information to be output by the device over the interface
10 is shown on the display of the PDA. This presupposes that the display capacity of the external display device, i.e., the PDA, for example, is known to the device delivering the information, e.g., a radio receiver having a TMC message decoder. This information may be requested by the radio
15 receiver from the external display unit, e.g., via the Bluetooth interface.